


EPS20TDE

Article code: 981112014



Europower super-silenced generating sets with Kubota water-cooled diesel engines, 1500rpm, 50Hz, 4 stroke

Generator:

kVA max.:	19
kVA cont.:	18
kVA:	6.7kVA @ 1~230V 18kVA @ 3~400V
Amps cont.:	29A @ 1~230V 26A @ 3~400V
Dimensions l x w x h:	198x74x100cm
Dry weight:	645kg
Weight incl. oil (+ coolant if water-cooled), excl. fuel:	660kg
Weight incl. oil (+ coolant if water-cooled) + fuel:	728kg

Engine:

Brand/Type:	Kubota V2203M E4BG2-EUP-1
HP max.:	23
Power:	17kW max. (1500rpm), 4-cylinder Diesel, Water-cooled
Displacement:	2197cm ³
Consumption @75% load:	3.7 litres/hour
Tank:	80 litres
Autonomy @75% load:	21.6 hours
Noise level:	65dB(A)@7m = Lwa 90
Electronic speed governor:	Standard
EU Emission norm:	Stage V
Battery voltage:	12V
CO2 emission:	0 g/kWh

Alternator:

Brand/Type	Leroy Somer LSA40M5 - brushless
Nominal voltage:	3~400V and 1~230V
Frequency:	50Hz
Protection degree:	IP23

www.EUROPOWERGenerators.com

Version:

- 2 sockets 230V - 16A + 1 socket CEE 230V - 16A + 1 socket CEE 230V - 32A + 1 socket CEE 400V - 16A 5 p. + 1 socket CEE 400V - 32A 5 p.
- Automatic voltage regulator
- Central lifting eye
- Earth leakage protection 30mA with earth pin and 4m earth cable
- Electric start, maintenance free battery included
- Electronic speed governor
- Emergency stop
- Fuel pump 12V
- High temperature security
- Hour counter
- Leroy Somer alternator System 2 for tropical environment
- Low oil pressure control lamp
- Low oil pressure guard
- Magneto-Stop
- Mechanical fuel level meter
- Oil drain pump
- Thermal magnetic breaker
- Voltmeter

Powered by:



Your **EUROPOWER** dealer